

In the claims:

Following is a complete set of claims as amended with this Response.

1. (Currently Amended) An apparatus ~~including a wireless access communication unit~~ comprising:

a trunk interface unit having a plurality of subscriber ports, each port being coupled to a trunk of a central telephone switch

a plurality of subscriber line interface cards, each coupled to a subscriber port to provide loop interface functions to the central telephone switch;

a subscriber interface module associated with each subscriber line interface card;

a radio transceiver to communicate with a wireless cellular communications network using a wireless trunk; ~~and~~

a control section coupled to each subscriber line interface card, to each of the subscriber interface modules, and to the radio transceiver to receive voice and signaling from each of the subscriber line interface cards to package and format the received voice and signaling for the wireless communications network and, using the subscriber interface modules, to coordinate and control over the air protocols of the wireless communications network, and

~~wherein the a~~ wireless access communications unit to route ~~routes~~ calls from user stations coupled to the central telephone switch to the wireless cellular communications network in response to a command received from the central telephone switch. .

2. (Previously Presented) The apparatus of Claim 1, wherein the trunk interface couples the wireless access communication unit to the central telephone switch using a wired trunk.

3. (Original) The apparatus of Claim 1, wherein the command received from the central telephone switch is based on a dialed number for the call received from the user station.

4. (Previously Presented) The apparatus of Claim 1, wherein the control section manages the transfer of data between the subscriber line interface cards and the radio transceiver.

5. (Currently Amended) The apparatus of Claim 4, wherein the control section controller is further to convert data received from a user station through a subscriber port to a format suitable for wireless transmission using the radio transceiver.

6. (Previously Presented) The apparatus of Claim 1, wherein the wireless access communication unit registers each trunk with the wireless cellular communications network so that each trunk appears as a subscriber to the wireless cellular communications network.

7. (Original) The apparatus of Claim 1, wherein the wireless access communication unit performs off-hook detection for outgoing calls and supports provision of a dial tone to the central telephone switch.

8. (Original) The apparatus of Claim 7, wherein the wireless access communication unit further initiates acquisition of a wireless communication channel on the wireless communications network and detects dialed address digits from a user station and passes the received digits via call control signaling to the wireless communications network.

9. (Original) The apparatus of Claim 7, wherein the wireless access communication unit detects off-hook transitions from the switch and initiates call release procedures towards the wireless communications network in response to the detected off-hook transition.

10. (Original) The apparatus of Claim 1, wherein the wireless access communication unit further comprises a line manager to handle communication between the wireless access communication unit and the switch including call signaling, dialed digit recognition, and transfer of collected dialed digits.

11. (Original) The apparatus of Claim 10, wherein the wireless access communication unit further comprises an over-the-air manager coupled to the line manager to handle communication interface and link management to the base station.

12. (Original) A method comprising:  
receiving a command from a central telephone switch at a wireless access communication unit, the switch being coupled to user stations;  
routing calls from user stations coupled to the switch alternately to a wireless cellular communications network using a wireless trunk or to a wired switched telephone network in response to the received command.

13. (Original) The method of Claim 12, wherein receiving the command comprises receiving a dialed number from a user station through the switch.

14. (Original) The method of Claim 12, further comprising converting data received at the wireless access unit from a user station through the switch to a format suitable for wireless transmission to the wireless cellular communications network.

15. (Currently Amended) The method of Claim 12, further comprising registering the wireless trunk between the wireless access communications unit and user stations with the wireless cellular communications network so that the wireless each trunk appears as a subscriber to the wireless cellular communications network.

16. (Original) The method of Claim 12, further comprising at the wireless access communication unit performing off-hook detection for outgoing calls and provisioning of a dial tone to the switch.

17. (Original) The method of Claim 16, further comprising at the wireless access communication unit initiating acquisition of a wireless communication channel on the wireless communications network and detecting dialed address digits from a user station and passing the received digits via call control signaling to the wireless communications network.

18. (Original) The method of Claim 16, further comprising at the wireless access communication unit detecting off-hook transitions from the switch and initiating call release procedures towards the wireless communications network in response to the detected off-hook transition.

19. (Original) A machine-readable medium having stored thereon data representing instructions which, when executed by a machine, cause the machine to perform operations comprising:

receiving a command from a central telephone switch at a wireless access communication unit, the switch being coupled to user stations;

routing calls from user stations coupled to the switch alternately to a wireless cellular communications network using a wireless trunk or to a wired switched telephone network in response to the received command.

20. (Original) The medium of Claim 19, wherein receiving the command comprises receiving a dialed number from a user station through the switch.

21. (Original) The medium of Claim 19, further comprising instructions which, when executed by the machine, cause the machine to perform further operations comprising converting data received at the wireless access unit from a user station through the switch to a format suitable for wireless transmission to the wireless cellular communications network.

22. (Original) The medium of Claim 19, further comprising instructions which, when executed by the machine, cause the machine to perform further operations comprising performing off-hook detection for outgoing calls and provisioning of a dial tone to the switch.

23. (Currently Amended) An apparatus comprising:

- a central telephone switch coupled to a plurality of user stations;
- a trunk interface unit having a plurality of subscriber ports, each port being coupled to a trunk of the central telephone ~~switch~~; ~~switch~~
- a plurality of subscriber line interface cards, each coupled to a subscriber port to provide loop interface functions to the central telephone switch;
- a subscriber interface module associated with each subscriber line interface card;
- a radio transceiver to communicate with a wireless cellular communications network using a wireless trunk; and
- a control section coupled to each subscriber line interface card, to each of the subscriber interface modules, and to the radio transceiver to receive voice and signaling from each of the subscriber line interface cards to package and format the received voice and signaling for the wireless communications network and, using the subscriber

interface modules, to coordinate and control over the air protocols of the wireless communications network,

wherein the wireless access communications unit routes calls from user stations coupled to the central telephone switch to the wireless cellular communications network in response to a command received from the central telephone switch. .

24. (Original) The apparatus of Claim 23, wherein the central telephone switch is configured to route a call alternately to the wired switched telephone network or the wireless access communication unit in response to a dialed number for the call received from the user station.

25. (Original) The apparatus of Claim 23, wherein the central telephone switch comprises a private branch exchange.

26. (Previously Presented) The apparatus of Claim 23, wherein the control section manages  
the transfer of data between the subscriber line interface cards and the radio transceiver.